



## PORTABLE EVAPORATIVE COOLING UNITS

[www.port-a-cool.com](http://www.port-a-cool.com)

### EVAPORATIVE COOLING UNITS ARE THE SOLUTION TO COOLING THOSE HARD TO COOL AREAS !

- Works where traditional air conditioning is not practical; lowers ambient temperature by an average of 20 degrees
- Inexpensive to operate (110 volt electrical & tap water) and environmentally friendly
- One piece molded plastic housing - no leaks
- Units sized to fit through standard door openings and are completely portable
- Garden hose (3/4") connection supplies water



Part Number	Blade Dia (in)	Motor HP	# of Speeds	Tank (gal)	Cooling Capacity (sq ft)	CFM Output
<b>48-2K482S</b>	48"	1 HP	2	40	<b>4,000</b>	<b>11,000 to 20,000</b>
<b>36-2K36HPVS</b>	36"	1/2 HP	Variable	32	<b>2,650</b>	<b>Up to 10,100</b>
<b>36-2K363S</b>	36"	1/2 HP	3	32	<b>2,500</b>	<b>4,800 to 9,600</b>
<b>36-2K361S</b>	36"	1/2 HP	1	32	<b>2,500</b>	<b>9600</b>
<b>24-JS2400</b>	24"	1/3 HP	Variable	48	<b>2000</b>	<b>Up to 7,500</b>
<b>24-2K24HPVS</b>	24"	1/3 HP	Variable	14	<b>1,800</b>	<b>Up to 6,700</b>
<b>16-JS1600</b>	16"	1/3 HP	Variable	42	<b>1000</b>	<b>Up to 4,900</b>
<b>16-163SVT</b>	16"	1/2 HP	3	42	<b>900</b>	<b>Up to 3,900</b>
<b>2KCYC01</b>	Centrifugal	1/3 HP	2	18	<b>700</b>	<b>2,400 to 1,350</b>

Part Number	Unit dimensions (in)			Power (110 Volt) Current (amps)	Shipping Wgt (lbs)
	Height	Width	Depth		
<b>48-2K482S</b>	6	74	36	13.7	405
<b>36-2K36HPVS</b>	67	62	32	11.3	240
<b>36-2K363S</b>	67	62	32	11.5	245
<b>36-2K361S</b>	67	62	32	12.4	235
<b>24-JS2400</b>	72	55	28	9.2	240
<b>24-2K24HPVS</b>	53	50	25	9.5	175
<b>16-JS1600</b>	59	38	24	5.3	140
<b>16-163SVT</b>	59	38	23	5.1	145
<b>2KCYC01</b>	38	29	30	5.6	100

Technical Support (1-888-266-5243) along with a complete line of Accessories (cover, water tank, ducting) & Replacement Parts (casters, filters, cooling pads) are available to keep your unit cooling well into the future